

# Village of Westchester

10300 West Roosevelt Road, Westchester, IL 60154 Phone: (708) 345-0199 • Email: Building@westchester-il.gov

## **APPLICATION FOR COMMERCIAL CONCRETE PERMIT**

Date Received				

	Date:		_ Site Address:	
Name of	Property Mana	ger/Owner:		Phone:
Address:				Email:
General Contractor:				Phone:
Contractor Address:				Email:
Downit Force	<b>D</b>	06/ef:	DESCRIPTION OF W	
Permit Fees:	Other Concre	t <b>e:</b> \$50 (stairs, v	• • •	\$50*** Curb Cut: \$30***  cost of job, minimum \$100 (includes plan review)  of job, minimum \$100
	eposit of \$250.00	is required for a	ny work adjacent to a stre	
•	es: \$100 each (3 Fees: In addition		Anv resubmittals are sub	oject to a \$55 re-review fee
	eposit: 1% cost o	•	•	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Driveway:	□ Concrete	□ Asphalt	☐ Paving Bricks	□ Curb Cut
Flat Work:	□ Sidewalk	□ Patio	□ Stairs	□ Stone/Brick Wall □ Other
relieve the applica	nt from constructing th	e work in any other n	nanner than that provided for in	been approved by the Building Commissioner or not, shall permit to the Ordinance of this Village relating thereto. The Applicant having nade are true to the best of my knowledge and belief.
Signature:			Da	te:
Print Name: _				

### **Application Requirements:**

- **Application Form**: Fill out a copy of this application form.
- **Current Plat of Survey**
- Proposed Site Plan: Two copies of proposed site plan showing a sketch of the proposed work and all size & setback dimensions.
- Contractor must be registered with The Village of Westchester and provide a signed contract with detail scope of work.
- Call JULIE (Joint Utility Locating Information for Excavators) at 1-800-892-0123 allowing 48 hours to locate utilities

PLEASE NOTE: IF YOU WILL HAVE A DUMPSTER ON SITE, A SEPARATE DUMPSTER PERMIT IS REQUIRED.TWO TIER MAXIMUM ON ALL ROOFS.

## **Concrete Construction Requirements for Westchester**

## **INSPECTIONS:**

You must contact the Building Department (708-345-0199) and schedule the necessary inspections.

- **Pre-pour Inspection:** Before pouring or covering of any flatwork.
- Final Inspection: A final inspection is required.
- ROW Inspection: An inspection to verify no damage to the public right of way must be scheduled to receive a
  refund.

### **CODE SPECIFICATIONS:**

- Curbs: Any mountable (roll over) curb at the driveway shall be required to be replaced with a depressed curb
  and gutter. Curb removal and replacement shall be accomplished by saw cutting and removing the limits of
  existing curb and gutter and replaced with a depressed curb and gutter, "Sawing off" the top of the curb will
  NOT be allowed.
- Driveway Approaches (portion between sidewalk and curb): Concrete ONLY
- Concrete: All concrete shall be 6 bag mix (4000psi) for flat work and 5 ½ bag mix (3500psi) for footings and foundations. All air entrained.
- **Driveway Pitch:** Driveway must be pitched for proper drainage. If adjacent to foundation, top of driveway to be 4" below top of foundation.
- Approach, public sidewalk and garage slab: 5" thick concrete over 4" compacted gravel fill. Welded wire mesh (6 x 6 x W1.4 x W1.4) 2-1/2" below surface. ½" expansion joints at the sidewalk and curb. (WWM not required on sidewalk)
- **Driveway and other flat work:** Minimum of **5**" thick concrete over 4" compacted gravel fill. Control joints every **12** to **15** feet. ½" expansion joints at garage apron, public sidewalk and against house foundation. (**WWM is** required on driveway)
- Asphalt: Base course shall be 4" of thoroughly compacted gravel. Surface course 2" minimum
- Brick Pavers @ drive: 10" CA6, 1 2" sand or limestone.
- Brick Pavers @ patio: 6" stone, 1 2" sand.

DUMPING OR PLACEMENT OR BROKEN CONCRETE OR GRAVEL ON THE STREET IS NOT ALLOWED.
VIOLATION MAY RESULT IN THE LOSS OF THE GUARANTEE DEPOSIT.